

100V Public Address System Volume Control

VC-C6 (6W)

VC-C30 (30W)

VC-C60 (60W)

VC-C120 (120W)



Features:

- PA (Public address) system use volume controller.
- Background music system use attenuator.
- Power control of 6W, 30W, 60W and 120W.
- Integrate with transformer technology of compact size.
- The volume controller is used to adjust the loudspeaker output in the room.
- The volume controller is used to keep same output level for one same speaker line, because the end the speaker line signal loss is rather big, so its outputs is less, thus volume controller is added to the front of the line to lower the speaker output so as to keep the similar ambient output level for the all of the speaker in the same line.
- High level white UV-protected ABS material to integrate together with the white wall and architecture design.
- Built-in transformer to control the PA 100V line loudspeakers.
- With 10 levels of volume attenuator and one position of off.
- Surface wall mount or in-wall mounting box shall be purchased separated.
- With 24V relay is optional.

Specification:

Model	VC-C6	VC-C30	VC-C60	VC-C120
Description	100V Volume Controller			
Rated Output	6W	30W	60W	120W
Line Input	100V or 70V			
Volume Step	5 steps			
Attenuation Per Step	3dB			
Total Attenuation	33dB			
Material	UV-protected ABS			
Finish	White			
Mounting Way	Surface mount or in-wall mount			
Depth	50mm	60mm	60mm	60mm
Plate Dimension	86(W)×86(D)mm			