


TL6ZT

МУЗЦЕНТР
МУЗЫКАЛЬНОЕ ОБОРУДОВАНИЕ
<https://muzcentre.ru>

Presentation:



The TL6ZT is a Public address amplifier with 6 independent channels/inputs delivering each input 150W rms.


This amplifier features 6 independent balanced audio inputs with independent volume controls on the front panel, each input in balanced XLR 3p microphone + respective Euroblock terminal inputs and 6 outputs in high impedance 100V line transformer with binding-post. It is equipped with an advanced protection circuit which protects against DC short circuit and overload when necessary for better performance on both fixed and mobile public address installations, being the perfect choice for supermarkets, warehouses, medical centres, etc. where there is a need to control each zone independently.

Solid construction for 19" rack - 3U mounting

Features:

- High quality PA amplifier
- Multizone installation PA amplifier
- 4 Microphone inputs with Balanced XLR
- 4 Euroblock terminal inputs
- Constant-voltage outputs (100V)
- Independent zone control (six)
- Individual volume control on the front panel
- Built-in electronic protection circuitry
- Solid construction for 19" rack - 3U mounting

Rear view:



Technical specifications:

Type	Professional PA mixer-amplifier
No. of channels	6 (six)
RMS Power @ 8ohm	150W (rms) per channel
Frequency Range	50Hz - 15kHz, ±0.3dB
T.H.D.	< 1.0% @ 1kHz
S/N ratio	> 90dB @ 1kHz
Zones	6 (six)
Controls	Master volume
Indicators	Power on, Signal
Inputs	Microphone
Outputs	High impedance, 100V
Connectors	Input: XLR 3p, Euroblock terminals Output: touch-proof binding post
Phantom Power	N/A
AC input	AC cable
Protections	Thermal overload, short circuit, temperature control
Operating Voltage	220-240V AC (factory configured), 50-60 Hz
Power consumption	900VA
Cooling	Continuous speed fan, 120mm / 230V AC
Dimensions	3RU space, 460mm (18.11in) depth
Weight	23Kg 50.71lb

